

Ref. SFOL170M-10



17" Foldable LCD-TFT Professional Monitor with 70 degrees inclination,



*Designed to be integrated
into a meeting and conference
Boardroom tables*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules
08551 - Tona - BARCELONA
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24
www.soltec-ep.com

DISPLAY

Panel Technology	Edge LED
Display Area (mm)	337,92(H) x 270,33(V)
Size	17,0"
Pixel Pitch (mm)	0,264 x 0,264
Screen Aspect	5:4
Native Resolution	1280 x 1024
Viewing Angle UDLR	80°/80°/85°/85°
Contrast ratio	800:1 (Typ)
Brightness cd/m2	350 (Typ)
Colors	16,7 M Colors
Response Time	30ms Ton +Toff
Protective Glass	3mm with black border
Life Time (hours)	50.000

CONNECTIVITY

Analogue RGB input	1xDB15
Digital Input	1xDVI
Plug & Play	VESA DDC2Bi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Supply adapter	12VDC - 5A
LCD Consumption	25W
Energy Management	VESA DPMS

MECHANICAL (mm)

Screen	401,5 x 406
On Table Cover plate	441,5 x 446
Under Table Housing	401,5 x 406 x 147
Tilt	70° tilt ajustment
Weight (Kg)	13

ENVIRONMENTAL CONDITIONS

Operation Temperature	-30° to 85°
Storage Temperature	-30° to 85°
Operation Humidity (%)	8 to 90
Storage Humidity (%)	8 to 90

OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord 12VDC Power adaptor Installation Manual

OPTIONS

RS-232 Control	1xDB9
RS-485 Control	2xRJ45 (With Loop)
Touch Screen	Projected Capacitive
CVBS + S-Video Inputs	1xRCA / 1xMiniDIN
Display Port	DP 1.1a
Customized Housing	Colors, Metal, Logo...

Specifications subject to changes without previous notice