

Media

Scale-1 Cam

Passive, point source with cam in line source enclosure, 4" woofer / 0.75" tweeter / Fohhn Sub Extension, 50 W, 104 dB SPL max.



Media Scale-1 Cam

Scale-1 Cam from the media series is a speaker system with woofer, tweeter and Fohhn Sub Extension. It offers broadband playback with powerful bass, even without an additional subwoofer. A conference camera (e.g. Huddly Cam) can be incorporated in the middle of the enclosure. When mounted vertically next to a screen, the camera is at the optimum height in the room. Another special feature of our Scale systems: If required, we can customise the enclosure length to fit your screen. The system is driven by our required system amplifier MA-4.100. Thanks to integrated speaker presets, this ensures operational safety and the desired performance.

Main features

- 4" long excursion driver / 0.75" dome tweeter / Fohhn sub extension
- Different camera models applicable
- Power rating (nominal): 50 W
- Maximum SPL: 104 dB
- Frequency range: 44 Hz – 20 kHz
- Special colours available
- 2 slot nuts included in scope of delivery
- Camera cover in the form of a black magnetic film (7 cm diameter) included
- Enclosure length: 830 - 1413 mm
- Attention: The loudspeaker can be operated with Fohhn system amplifiers and the correct speaker preset only.

Available with the following color options



Black

Equipped with the following Fohhn technologies



Fohhn Texture Design



Special colors optional



Scalable enclosure

Technical data

Electroacoustic features

acoustic design	compact 2-way speaker with extended lowend
power rating (nominal)	50 watts
power rating (program)	100 watts
power rating (peak)	200 watts
components	4" woofer / 0.75" dome tweeter / Fohhn Sub Extension
maximum SPL	104 dB
nominal dispersion (h × v)	140° × 90°
frequency range	44 Hz – 20 kHz
nominal impedance	4 Ohm

Features

enclosure	aluminum
front design	metal grille in enclosure colour
protection grille	steel grille, ball impact resistant, powder-coated
standard colours	black or white powder-coated
mounting points	continuous T-slot at rear
connectors	2 × 2-pin phoenix terminal
dimensions (W × H × D)	133 × 830 (up tp 1413) × 128 mm

Optional features

optional colours	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
------------------	--------------------------------------------------------------

CAAD simulation data

simulation data	Fohhn Designer
-----------------	----------------

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range

frequency range: -10 dB under anechoic halfspace-conditions

weight: net weight without optional equipment

nominal dispersion (h × v): -6 dB compared to the main dispersion axis, averaged 1 – 4 kHz

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

