



BUZZER FLASH LIGHT

FL-200

This portable unit adds more versatility to the Altair E-200 serie Intercom system as it allows to recognize a call in noisy and complex environments.

The unit remotely feeds itself as in the beltpack mobile units and carries an additional connector to chain more extensions to the line.

As in the rest of the system, a high sound buzzer with switch on/off selector from the front panel, as the switch off remote function from the central unit or buzz-kill function for its application in silent environments.

CHARACTERISTICS

- Amber colour High efficiency xenon flash light
- High sound buzzer (2 levels intern adjust and switch off)
- Robust and light metallic structure
- Multipurpose holding clip
- 3 working ways :
 - light & sound warning (predetermined at the start)
 - light warning with buzzer switch off (short pressing buzzer key)
 - sound warning with switch off light (extended pressing buzzer key)
- remote powered from the central unit station (EF-200) trough Intercom standard cables

TECHNICAL SPECIFICATIONS

- Flash frequency : 60 per minute
- Calling minimum duration : 7 seconds or 7 flashes
- Visibility : 360 degrees
- Sound level : 90/100 dbA
- Supply tension 20-30 VDC ,24 VDC nominal
- Consumption : 10-70 mA at 24 VDC
- Dimension/weight : 84x88x130 mm/330 net gr



EQUIPOS EUROPEOS ELECTRÓNICOS, S.A.L.

Avda. de la industria, 50 - 28760 TRES CANTOS - MADRID - SPAIN
www.altairaudio.com - e-mail:altair@altairaudio.com - Tel: +34 91 761 65 80 - Fax: +34 91 804 43 58